



Approval Number

E 4 0105 TYPE 260

Pos	Qty	Part No.	Description	Ordernumber
1	1	900023	Muffler HyperFox Oval 110 Carbon Steel	HO06C05-HFCS - Carbon Steel
1	1	900051	Muffler HyperFox Oval 110 Shot Blasted	HO06C05-HFSB - Shot Blasted
1	1	900052	Muffler HyperFox Oval 110 Black Coated	HO06C05-HFBC - Black Coated
1	1	900077	Muffler HyperFox Oval 110 Stainless Steel	HO06C05-HFST - Stainless Steel
		850024	Mounting Parts:	Weight:
2	1	72113	Link Pipe	Stock: 6,1 kg
3	1	64595	Mounting Bracket	Bos: 4,2 kg
4	2	14140	Bolt Flange M6x16	Noiselevel: @ 4000 rpm
5	2	14087	Pull Spring 48 mm.	Stock: Specified 84,0 dB(A)
				Measured 84,0 dB(A)
				Bos: With DBeater 85,0 dB(A)
				Open 91,0 dB(A)

Performance

Stock: 82,6 Hp / 11954 rpm
 Bos: 85,6 Hp / 11567 rpm
 Max. Hp incr.: + 4,1 Hp / 11537 rpm
 Max Nm incr.: + -, - Nm / - - - - rpm

Tips

In order to avoid smudges and fingerprints burning into the surface it is imperative to clean the exhaust before starting the engine, burnt in stains are very difficult to remove.
 After 300 miles or 500 kms. check all nuts and bolts and retighten if necessary.