



Approval Number

E 4 0105 TYPE 260

| Pos | Qty | Part No. | Description | Ordernumber |
|-----|-----|---------------|---|---------------------------------------|
| 1 | 1 | 900023 | Muffler HyperFox Oval 110 Carbon Steel | HO06C05-HFCS - Carbon Steel |
| 1 | 1 | 900051 | Muffler HyperFox Oval 110 Shot Blasted | HO06C05-HFSB - Shot Blasted |
| 1 | 1 | 900052 | Muffler HyperFox Oval 110 Black Coated | HO06C05-HFBC - Black Coated |
| 1 | 1 | 900077 | Muffler HyperFox Oval 110 Stainless Steel | HO06C05-HFST - Stainless Steel |
| | | 850024 | Mounting Parts: | Weight: |
| 2 | 1 | 72113 | Link Pipe | Stock: 6,1 kg |
| 3 | 1 | 64595 | Mounting Bracket | Bos: 4,2 kg |
| 4 | 2 | 14140 | Bolt Flange M6x16 | Noiselevel: @ 4000 rpm |
| 5 | 2 | 14087 | Pull Spring 48 mm. | Stock: Specified 84,0 dB(A) |
| | | | | Measured 84,0 dB(A) |
| | | | | Bos: With DBeater 85,0 dB(A) |
| | | | | Open 91,0 dB(A) |

Performance

Stock: 82,6 Hp / 11954 rpm
 Bos: 85,6 Hp / 11567 rpm
 Max. Hp incr.: + 4,1 Hp / 11537 rpm
 Max Nm incr.: + -, - Nm / - - - - rpm

Tips

In order to avoid smudges and fingerprints burning into the surface it is imperative to clean the exhaust before starting the engine, burnt in stains are very difficult to remove.
 After 300 miles or 500 kms. check all nuts and bolts and retighten if necessary.