



Approval Number

E 4 0105 TYPE 260

Pos	Qty	Part No.	Description	Ordernumber
1	1	900023	Muffler Hyperfox Oval 110 S150 Carbon Steel	HO6C02-HFCS Carbon Steel
1	1	900052	Muffler Hyperfox Oval 110 S150 Black Coated	HO6C02-HFBC Black Coated
1	1	900051	Muffler Hyperfox Oval 110 S150 Shot Blasted	HO6C02-HFSB Shot Blasted
1	1	900077	Muffler Hyperfox Oval 110 S150 Stainless Steel	HO6C02-HFST Stainless Steel
		80019	Mounting Parts:	
2	1	72198	Link Pipe	
3	1	64596	Mounting Bracket	
4	2	14140	Bolt M6x16	
5	2	14087	Pull spring 48mm	
6	1	64014	Clamp 47	
				Weight:
				Stock: 7,0 kg
				Bos: 3,1 kg
				Noiselevel: @ 6000 rpm
				Stock: Specified 87,0 dB(A)
				Measured 87,0 dB(A)
				Bos: EC Appr. 88,0 dB(A)
				Open 92.3 dB(A)
				Performance
				Stock: 86.0 Hp / 11354 rpm
				Bos: 81,6 Hp / 11341 rpm
				Max. Hp incr.: + 4,6 Hp / 11452 rpm

Extra Parts:

50035 DBeater Ø28 Hyper

Tips:

In order to avoid smudges and fingerprints burning into the surface it is imperative to clean the exhaust before starting the engine, burnt in stains are very difficult to remove.

After 300 miles or 500 kms. check all nuts and bolts and retighten if necessary.