



Approval Number

E 4 2403 (9) TYPE 1004

Pos	Qty	Part No.	Description	Ordernumber
1	1	900053	Muffler HyperFox Ov120 S150 Shot Blasted	HO12V02-HFSB - Shot Blasted
1	1	900089	Muffler HyperFox Ov120 S150 Carbon Steel	HO12V02-HFCS - Carbon Steel
1	1	900063	Muffler HyperFox Ov120 S150 Black Coated	HO12V02-HFBC - Black Coated
		80226	Mounting Parts:	Weight:
2	1	72250	Link Pipe #1	Stock: 5,9 kg
3	1	72251	Link Pipe #2	Bos: 4,3 kg
			Mounting Kit:	Noiselevel: @ 5000 rpm
4	1	64451	Mounting Bracket	Stock: Specified 95,0 dB(A)
4	1	64652	Mounting Bracket (use with sidecases)	Measured 93,8 dB(A)
5	2	14049	Bolt M6x16	Bos: With DBeater 92,3 dB(A)
6	1	14129	Washer M12	Open 96,5 dB(A)
7	2	14087	Pull Spring 48 mm.	
8	1	64014	Clamp 47	
9	1	64653	Clamp 53	
10	1	Original	Original Bushing	
Extra Parts:				Performance
		650079	DBeater Ø32 Hyper Restriction	Stock: 163,7 Hp / 9445 rpm
				Bos: 151,9 Hp / 9421 rpm
				Max. Hp incr.: + 13,5 Hp / 8730 rpm
				Max Nm incr.: + 26,6 Nm / 2927 rpm

Tips

In order to avoid smudges and fingerprints burning into the surface it is imperative to clean the exhaust before starting the engine, burnt in stains are very difficult to remove.
After 300 miles or 500 kms. check all nuts and bolts and retighten if necessary.