



Pos	Qty	Part No.	Description	Ordernumber
1	1	900024	Muffler BOS Oval 120 Stainless	<b>1311608S - Stainless</b>
1	1	900025	Muffler BOS Oval 120 Carbon Steel	<b>1311608Cs - Carbon Steel</b>
		<b>80258</b>	<b>Mounting Parts:</b>	
2	1	73160	Link Pipe	<b>Weight:</b>
				<b>Stock:</b> 7,5 kg
				<b>Bos:</b> 4,4 kg
3	1	64747	Mounting Bracket	<b>Noiselevel: @ 5100 rpm</b>
4	2	14140	Bolt M6x16	<b>Stock:</b> Specified 91,0 dB(A)
5	2	14087	Pull Spring 48 mm.	Measured 89,0 dB(A)
6	1	64748	Mounting Bracket LP	<b>Bos:</b> With DBeater 90,7 dB(A)
7	1	14058	M8 Spring Washer	Open 99,7 dB(A)
8	1	14063	Bolt M8x12	
<b>Performance</b>				
Stock: 103,0 Hp / 10383 rpm				
Bos: 105,6 Hp / 10548 rpm				
Max. Hp incr.: + 3,2 Hp / 8766 rpm				
Max Nm incr.: + 3,7 Nm / 4600 rpm				
<b>Extra Parts:</b>				
		50119	Dbeater Ø32 Hyper	

#### Tips

In order to avoid smudges and fingerprints burning into the surface it is imperative to clean the exhaust before starting the engine, burnt in stains are very difficult to remove.

After 300 miles or 500 kms. check all nuts and bolts and retighten if necessary.