



Pos	Qty	Part No.	Description	Ordernumber
1	1	900020	Muffler Bos Oval Cs	0811080Cs - Carbon Steel
		80003	Mounting Parts:	Weight:
2	1	72182	Link Pipe	Stock: 5,0 kg
3	1	64539	Mounting Bracket	Bos: 3,5 kg
4	2	14049	Bolt M6x16	Noiselevel F650GS: @ 3500 rpm
5	1	14092	Rubber	Stock: Specified 87,0 dB(A)
6	1	64621	Bushing	Measured 86,5 dB(A)
7	1	14066	Bolt M8x25	Bos: With DBeater 85,5 dB(A)
8	1	14060	Washer M8	Open 93,2 dB(A)
9	2	14087	Pull Spring 48 mm.	Performance F650GS
10	1	64560	Clamp 55-59	Stock: 65,8 Hp / 7066 rpm
				Bos: 67,1 Hp / 7280 rpm
				Max. Hp incr.: + 2,4 Hp / 6180 rpm
				Max Nm incr.: + 2,6 Nm / 6230 rpm
				Noiselevel F800GS: @3750 rpm
				Stock: Specified 88,0 dB(A)
				Measured 87,6 dB(A)
				Bos: With DBeater 87,4 dB(A)
				Open 94,4 dB(A)
				Performance F800GS
				Stock: 78,2 Hp / 7565 rpm
				Bos: 80,9 Hp / 7561 rpm
				Max. Hp incr.: + 4,3 Hp / 8178 rpm
				Max Nm incr.: + 5,7 Nm / 2204 rpm

Tips:

In order to avoid smudges and fingerprints burning into the surface it is imperative to clean the exhaust before starting the engine, burnt stains are very difficult to remove.

After 300 miles or 500 kms. check all nuts and bolts and retighten if necessary.