



Approval Number

E 4 0105 TYPE 260

Pos	Qty	Part No.	Description	Ordernumber
1	1	900051	Muffler HyperFox Ov110 S150 Shot Blasted	SU06G01 - HFSB - Shot Blasted
1	1	900023	Muffler HyperFox Ov110 S150 Carbon Steel	SU06G01 - HFCS - Carbon Steel
1	1	900052	Muffler HyperFox Ov110 S150 Black Coated	SU06G01 - HFBC - Black Coated
		80055	Mounting Parts:	
2	1	72119	Link Pipe	
3	1	64413	Mounting Bracket	
4	2	14049	Bolt M6x16	
5	2	14087	Pull Spring 48 mm.	
6	1	64512	Standstop	
7	1	14090	Standstop rubber	
				Weight:
				Stock: 6,2 kg
				Bos: 3,8 kg
				Noiselevel: @ 5050 rpm
				Stock: Specified 90,0 dB(A)
				Measured 90,0 dB(A)
				Bos: EC appr. 91,0 dB(A)
				Open 95,0 dB(A)
				Performance
				Stock: 69,8 Hp / 10231 rpm
				Bos: 72,2 Hp / 10414 rpm
				Max. Hp incr.: + 6,3 Hp / 11827 rpm
				Max Nm incr.: + -, Nm / - - - - rpm
Extra Parts:				
		50035	DBeater Ø28 Hyper	

Tips

In order to avoid smudges and fingerprints burning into the surface it is imperative to clean the exhaust before starting the engine, burnt in stains are very difficult to remove.
After 300 miles or 500 kms. check all nuts and bolts and retighten if necessary.