



Approval Number

E 4 2281 (9) TYPE 7011

Pos	Qty	Part No.	Description	Ordernumber
1	1	900065	Muffler HyperFox OV120 S180 Shot Blasted	SU12G04 - HF SB - Shot Blasted
1	1	900075	Muffler HyperFox OV120 S180 Black Coated	SU12G04 - HF BC - Black Coated
1	1	900076	Muffler HyperFox OV120 S180 Carbon Steel	SU12G04 - HF CS - Carbon Steel
		80284	Mounting Parts:	
2	1	72188	Link Pipe	Weight: Stock: 6,6 kg Bos: 3,4 kg
3	1	64433	Mounting Bracket	
4	2	14140	Bolt M6x16	
5	2	14087	Pull Spring 48 mm.	Noiselevel: @ 3750 rpm
6	1	64518	Standstop	Stock: Specified 84,0 dB(A) Measured 84,2 dB(A)
7	1	14058	Lock Washer M8	Bos: With DBeater 84,5 dB(A) Open 86,0 dB(A)
8	1	14063	Bolt M8x12	
9	1	14090	Rubber	
10	1	64560	Clamp 57	Performance
Stock: 103,1 Hp / 8805 rpm Bos: 109,9 Hp / 8791 rpm Max. Hp incr.: + 6,7 Hp / 6831 rpm Max Nm incr.: + 11,8 Nm / 5528 rpm				

Extra Parts:

650079 DBeater Ø32 Hyper Restriction

Tips

In order to avoid smudges and fingerprints burning into the surface it is imperative to clean the exhaust before starting the engine, burnt in stains are very difficult to remove.
After 300 miles or 500 kms. check all nuts and bolts and retighten if necessary.